











Somany Ceramics Limited: Noida: F-36, Sector-6; Ph.: 0120-4627900.

Ahmedabad: Office no. 7-14, 4th Floor, Aggarwal Mall, Opp. Sola Bhagwat Vidyapeeth, S.G. Road, Sola, Ph.: 079-66042500 to 599 Registered office: 2, Red Cross Place, Kolkata - 700001; Ph.(033) 22487406/5913

www.somanyceramics.com | e-mail marketing@somanyceramics.com














# MARVELA COP FLOR UFF





800x800mm





## Natural marvels

for a wonderful abode

The new range of "Marvela" tiles by Somany is a fusion of elegance & grace. Inspired from Indian, Turkish & Italian marble, it offers plethora of designs, which can be marveled into natural masterpieces.

Available in 800x800mm size these high definition digital polished tiles provide gleaming mirror like finish. Complimented with designs that caters to both wall & floor, Marvela is also the toughest tile in its category.

With a wide range of textures, finishes, designs & sizes, Marvela is here to add absolute mix of sophistication & opulence lending a sheer bliss to ones's abode.





800x800mm | Full Polish Finish | Matt Finish | VC Finish PAGE NO. 04 16 26





























ROYALE ALLIER NATURAL FP



ROYALE ALLIER OLIVE FP



ROYALE ALLIER NERO FP




ROYALE AMALGA GREY FP



ROYALE CALINA CREMA FP



ROYALE CALINA NATURAL FP































ROYALE CREPA BEIGE FP



ROYALE MELANGE IVORY FP



ROYALE CREPA CREMA FP



ROYALE MONDO GRIS FP



ROYALE MIRACO GREY FP



ROYALE MIRACO NATURAL FP



10





























ROYALE SELVA BROWN FP



ROYALE VERSO CREMAFP



ROYALE SELVA GERIS FP




ROYALE VERSO GRIS FP



ROYALE WONDER BEIGE FP



ROYALE WONDER BROWN FP



15 \_






























ROYALE ASPERO CEMENT

ROYALE BRONCO BLANCO





ROYALE BRONCO CHOKO



ROYALE CLARIDDO BIANCO



ROYALE CLARIDDO MOKA


































ROYALE CONIFERO WOOD TEAK



ROYALE CONIFERO WOOD NATURAL




ROYALE CONIFERO WOOD WENGE



ROYALE CONIFERO WOOD NERO



ROYALE GLANZA CREMA



ROYALE GLANZA SLATE





































ROYALE ANNATAWOOD WENGE VC




ROYALE ARENISCA GREY VC



ROYALE FENOR BEIGE VC



ROYALE PENSER BIANCO VC



ROYALE ARENISCA BEIGE VC





26.

















### **Technical Specification**



#### **DESIGN, PATTERN & SHADE VARIATION GUIDE**


Current development efforts have made ceramic tiles to resemble and look authentically identical to natural material (Stone, Wood, Fabric), and it has become increasingly difficult in many cases, to distinguish between two.


Recognising this situation, it is necessary to be informed on the grade of design & pattern variation that is expected from the seproducts. As a general reference, the design & Pattern guide below classifies a scale of ranges according to the degree of variation.





Slight Variation





V1 Uniform Appearance

The classification is as follow

✓ Minimal Variation ✓ Random Variation ✓ Slight Variation ✓ Substantial Variation



High Definition Image

While laying the tiles please follow the arrow on the back of the tiles. For removing the wax from the surface of the tiles please use the soft cotton cloth for rubbing with any boric/talk powder



#### VEILCRAFT (VC) SHIELD

Not only look and style; the buzz word for the Gen X tile is timeless elegance. Here comes the revolutionary patented "VeilCraft (VC) Shield" technology, a 'high abrasion resistant glaze composition', known as VC (VeilCraft) Shield. This is the first ever patented technology in Indian Ceramic Industry. This not only gives you the perfect aesthetics for your space but also the lifelong protection to your floor.

#### Result Of The abrasion test at 25,000 revolutions as per the PEI Methodology













Patent Certificate for "High Abrasion Resistant Glaze" applied on VC Shield Tiles

100000	पेटेंट क	NT OF INDIA तर्यालय NT OFFICE माणपत्र	INTELLECTUAL PROPERTY INDIA AUSTONIA DEBUGATI PROPERTY INDIA AUSTONIA MARKATA MARKATANIA
	(Rule 24 of F		
Patent No.	13	227692	
Application No.	33	420/DEL/2005	
Date of Filing	1	25/02/2005	
Patentee		SPL Limited	
It is hereby certifican invention entitled COMPOSITION," as disterm of 20 years from the provisions of the Patents	"A HIGH closed in the 25 day of FEB	above mentioned ap	TANT GLAZE
Date of Grant: 16/01/2009	9.3	ca	MATOUER OF PATENTS
NoteThe fees for renes fallen due on 25 day of thereafter.			

	_
ELLECTUAL PERTY INDIA 11 DESERBI TRADE MARKE AMECAL DESCARDOR	
e for AZE r the h the	
itents	
all / hus ry year	

#### Glazed Floor Tile 800 x 800mm (HD Full Polished / Matt Finish) (Unit II) Test Method Table-07 3 < E ≤ 6 Gro sion & Surface Qualit Length & Width ±0.10% ±0.60% ± 0.10% ± 5.0 % ± 5.0% ± 4.0% Thickness Straightness of Side ± 0.10% ± 0.5% ± 0.10% Rectengularity ± 0.10% ± 0.6% ± 0.10% Surface Flatness Part 1 ± 0.5 % Center curvature (%) (max.Deviation) ± 0.5% ± 0.20% Edge curvature (%) ( max.Deviation) ± 0.5 % ± 0.5% ± 0.20% Corner warpage (%)( max.Deviation) ± 0.5 % ± 0.5% ± 0.2% Min. 95 % of tiles will be 95 % of tiles will be 95 % of tiles will be Surface Quality free from visible defects free from visible defects free from visible defects Physical Properties Average 3 <E≤6, Water Absorption (%) 3<E≤6, Individual max 6.5 3 to 4 Part 2 Modulus of Rupture [N/mm2] Av 22, Individual 20 min Avg 22 Individual 20 min 28 100 Part 6 Breaking Strength in N Min. 1100 Min.1000 Not less than 1000 Moisture Expansion in mm/m 0.03 mm/M max N.A 0.02 155 Part 3 Min 7 (commercial ), Min 5 (Home) Min 7 (commercial ). Scratch Hardness of surface (Mohs) 101 Part 13 N.A Matt Finish Min 5 (Home) polished 3 Resistance to Deep Abrasion of unglazed tiles Part 11 7 Resistance to Abrasion of Commercial application Min IV, Report Abrasion Depends on Glaze surface 154 Part 11 Home Application Min II glazed tiles( Class I to V ) Class & Cycle Passed Glossy polish PEI III, Coefficient of linear thermal expansion Test Method Available 103 Part 4 7 X 10<sup>-6</sup> K<sup>-1</sup> max 9 X 10<sup>-6</sup> K<sup>-1</sup> max from embiant temperature to 100 0 C 10 cycle min Test Method Available Passed 10 Cycle 104 Crazing Resistance 4 cycle @ 7.5bar min Required Passed 4 Cycle 104 Part 9 Forst resistance Required, if agreed Test Method Available 202 Part 10 **Bulk Density** 99 Part 2 Impact resistance NΑ Test Method Available N.A Part 14 Stain Resistance Min Class-1 Min Class-3 Min Class-1 Resistance to household chemicals Min Class AA Min Class GB Min Class AA Part 8 13 / 14 Resistance to acids and alkalis (with exception Manufacturer to state Required if agreed Min Class AA

PACKAGING DETAIL for 800 x 800mm						
Nominal Size	Thickness (mm)	Av. Wt. per carton (Kg)	No. of Tiles per carton	Coverage area per carton		
800X800 mm	10.8 (+/- 0.2)	30.0~31.0 Kg.	2	1.28 Sq.Mt/13.78 Sq.Ft.		

The reproduction of tiles in this catalogue is restricted to four color printing only and tiles are not in relative sizes, therefore customers are advised to see physical sample before placing the order. Technical Specifications for Somany Wall & Floor Tiles are applicable only for premium quality tiles. Please inspect all tiles prior to installation, company will not entertain complaints, once the tiles are laid/fixed. Complaints will not be entertained for Borders, Highlighters & Motifs.